# **XPRIME SERIES OF HF GENERATOR**

# PXP-16HF MICRO PORTABLE

SMALLEST & LIGHTEST WEIGHT: 14 LBS ONLY
SMARTER SOFTWARE: REMOTE CONTROLLER
SLIMLINE DESIGN & STRONG: PLASTIC MOLD COVER





## **FEATURES**


- ◆ Lightest weight & durable cover : 14 lbs only
- ♦ High frequency inverter type : 100 Khz
- ◆ Superb image quality : 1.0 mm focal size
- ◆ Constant potential radiation energy out put
- ◆ Remote Control Software & PROM memory
- ◆ Programmable Pre-set techniques
- Dual Laser pointer for Pre-set Auto focus
- Halogen lamp collimator & 4 blades
- ◆ Flat OP control panel & digital display LED
- ◆ DR interface & auto recognition
- ◆ Automatic line voltage compensation

# PXP-16HF

XPRIME SERIES OF PORTABLE X-RAY



### **DIMENSIONS**



### **DUAL LASER MODULE**

- -Best choices for perfect image presentation
- -Dual laser makes the most difficult radiographic Imaging easier by only taking one exposure without retaking a film repeatedly.



#### **SPECIFICATIONS**

#### GENERATOR

X-ray output: 16mA/80 KV 50-80 KV/ 1.0 KV step KV range: - mAs rang: 0.4-30 mAs Max. rating: 1.2 KW@80 KV - Inverter type: 100 KHz

#### CONTROL PANEL

- Digital LED display: mAs & KV
- Remote Control Software & PROM
- Programmable pre-set technique
- Data storage & store button
- LED indicator: Ready & Exp. Wait

#### X-RAY TUBE: Superior Tube

SXR-8--14-10 Insert: - Focal size: 1.0 mm 14 fixed target Anode: 7,000 HU Heat unit:

#### COLLIMATOR & DUAL LASER

- Type: Manual, 4 blades - Lamp: 50 watt, Halogen - Auto timer: 30 sec. Run-of timer 2.0 mm Al.eq.@80KV Filter: Pre-set focus (26") Dual Laser:

#### POWER REQUIREMENT

- Line volt: 110/220 VAC, 50/60 Hz
- Max. Current: 10-16 Amp.
- Input power: 1.8 KW@110 VAC

#### WEIGHT SPECIFICATION

- Net weight: 12.7 lbs

Gross weight: 23.0 lbs W/ Carrying Case



26" Auto Focus on Target

#### REMOTE CONTROL HAND SWITCH & SOFTWARE

The Remote Control Software(RCS) on all PXP-HF family portable x-ray unit allows total control of all exposure technique values such as PROM memory pre-sets, collimator light & laser pointer and exposure control functions right from your hand switch.

This allows you to make adjustments on the fly without placing your portable on the ground or fumbling for awkward dials and display panel controls. Very convenient for equine and large animal field use. This feature is standard on all PXP-HF series of portable units.





Exp. & Remote Control Hand Switch

All specifications are subject to change without notice



## UNITED RADIOLOGY SYSTEM, INC

Affiliated with POSKOM America, Inc. 151 Pfingsten Rd. Unit T, Deerfield, IL 60015

Distributed by

www.medicaltronik.ca

Tel: (847) 291-0999 Fax: (847)291-1090

Web site: www.united-radiology.com